



Textile Banner 1100

Made of 100% polyester, 220g/m² thickness, warp knit fabric with semi matt surface finish. The material is extraordinary in terms of:

- wrinkle free (recover quickly after folded), makes it easy to be transported;
- high opacity (due to special tight textile structure).

End use: Banners, exhibitions, display-systems, blinds.

Furnish: 100% polyester fabric.

Finish: Matt.

Ink compatibility: Dye sublimation; Latex.

Flame retardant: Yes, B1.

Technical Target Values

Properties	Test method	Units	Values
Total weight	ASTM D751	g/m ²	220
Yarn Dtex	ASTM D1907	Dtex	75x40x40
Shrinkage	N/A (190°C, 1min)	%	<=2
Recommend fixation temperature	N/A	°C, min.	(190°C-210°C, 1-2min)
Transfer temperature	N/A	°C, min.	190°C-210°C, 1-2min
Yellowing temperature	N/A	°C	>=210

Available Widths: 1050, 1600, 2100, 3200 mm.

Available cores: 3".

Available lengths of the roll: 100m.

Technical specs may change without prior notice.

UAB GM Media
Geležinio Vilko str. 18A,
LT-08104 Vilnius
Lithuania

Phone: +370 5 2652196
Fax.: +370 5 2784655
E-mail: info@gm-media.eu
www.gm-media.eu

Company ID: 302351061
VAT Registration Number:
LT100004772017
Bank: UAB Medicinos Bankas
SWIFT: MDBALT22
Account Number:
LT43 7230 0000 0446 7062