



Textile Mesh 1100

Made of 100% polyester, 290g/m² thickness, warp knit mesh fabric with matt surface finish. The material is extraordinary in terms of PVC-free option for mesh type media application.

End use: Hanging display, banner, wall wrapping, fence, etc.
Furnish: 100% polyester.
Finish: Matt.
Ink compatibility: Dye sublimation.
Flame retardant: Yes, B1.

Technical Target Values

Properties	Test method	Units	Values
Total weight	DIN EN ISO 2286-2, ASTM D751	g/m ²	290
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	Dtex	330x330
Shrinkage	N/A (210°C, 30s)	%	<=2
Tensile Strenght	DIN EN ISO 1421	N/5cm	1057x1292
Tear Strenght	DIN 53363	N	193x243
Recommend Fixation Temperature	N/A	°C, min.	(190°C-210°C, 1-2min)
Yellowing Temperature	N/A	°C	>=210

Available Widths: 1050, 1600, 2100, 3200 mm.
Available cores: 3".
Available lengths of the roll: 50m.

Technical specs may change without prior notice.

UAB GM Media
Geležinio Vilko str. 18A,
LT-08104 Vilnius
Lithuania

Phone: +370 5 2652196
Fax.: +370 5 2784655
E-mail: info@gm-media.eu
www.gm-media.eu

Company ID: 302351061
VAT Registration Number:
LT100004772017
Bank: Luminor Bank AB
SWIFT: NDEALT2X
IBAN: LT582140030003983557